

APEX® 1523E-8

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information						
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Uses	Automotive Window Encapsulation					
Automotive Specifications	• FORD WSK-M4D689-A6	GM GMP.PVC.074	• TOYOTA TSM 5728G-2			
Forms	• Pellets					
Processing Method	Injection Molding					

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.25		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	1650	psi	ASTM D638		
Tensile Elongation (Break)	430	%	ASTM D638		
Elastomers	Nominal Value	Unit	Test Method		
Tear Strength	199	lbf/in	ASTM D624		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	68		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	-34.6	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.