

18

- Thermoplastic Friday, June 30, 2017

General Information							
General							
Material Status	Commercial: Active						
Availability	 Africa & Middle East 	Asia Pacific	Latin America				
Features	Flame Retardant	 Halogen Free 					
Uses	 Insulation Shield 						
Forms	• Pellets						

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.47		ASTM D792		
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	6.0	g/10 min	ASTM D1238		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	2030	psi	IEC 811-1-1		
Tensile Elongation (Break)	100	%	IEC 811-1-1		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact	6.6	ft·lb/in	ASTM D256		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D)	47		ASTM D2240		
Electrical	Nominal Value	Unit	Test Method		
Surface Resistivity	5.0E+14	ohms	ASTM D257		
Volume Resistivity	4.0E+14	ohms·cm	ASTM D257		
Flammability	Nominal Value	Unit	Test Method		
Flame Rating (0.12 in)	V-0		UL 94		
Oxygen Index	32	%	ASTM D2863		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.