

- Polyethylene

291

Friday, June 30, 2017

General Information				
General				
Material Status	 Commercial: Active 			
Availability	 Asia Pacific 			
Filler / Reinforcement	Titanium Dioxide Equ	ivalent, 60% Filler by Weight		
Features	 General Purpose 			
Uses	• Film	Masterbatch		
Appearance	• White			
Forms	 Pellets 			
Processing Method	Blown Film	Sheet Extrusion		

Physical	Nominal Value Unit	Test Method
Specific Gravity	1.99	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	< 20 g/10 min	ASTM D1238
Moisture Content	< 0.25 %	ASTM D3030

Not recommended for outdoor application

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/19/2011