

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Uses	Appliance Wire Jacketing		
RoHS Compliance	RoHS Compliant		
Forms	• Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.40		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Yield)	2320	psi	IEC 811-1-1	
Tensile Elongation ² (Break)	300	%	IEC 811-1-1	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	77		ASTM D2240	
Aging	Nominal Value	Unit	Test Method	
Change in Tensile Strength (239°F, 504 hr)	10	%	IEC 811-1-2	
Change in Ultimate Elongation (239°F, 504 hr)	30	%	IEC 811-1-2	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/9/2014

¹ Typical properties: these are not to be construed as specifications.

² 9.8 in/min