

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Features	Good Stiffness	Oil Resistant		
Uses	Gaskets	Liners		
Forms	Granules			
Processing Method	Extrusion			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.25		ASTM D792	
Congo Red (374°F)	30.0	min	BS 2782	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	2320	psi	ASTM D638	
Tensile Elongation (Break)	400	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	65		ASTM D2240	

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex U.K. Ltd.
	Tat Bank Road
In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)	Oldbury, West Midlands B69 4NH England
505 Central Avenue	Phone: (44) 121-665-2100
Pawtucket, Rhode Island 02861 U.S.	Fax: (44) 121-544-5530
Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864	etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/7/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.