## - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	Ethylene Oxide Sterilizable		
Uses	Medical/Healthcare Applications		
Forms	• Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.24		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength <sup>2</sup> (Yield)	3190	psi	ASTM D638	
Tensile Elongation (Break)	340	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	81		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Thermal Stability (374°F)	> 30	min	ASTM D2115-92	

## **Notes**

## **Teknor Apex Company** Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

Phone: 401-725-8000

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/7/2014

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>&</sup>lt;sup>2</sup> 20 in/min