# **'58**

## - Rigid Polyvinyl Chloride

Thursday, June 29, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	Food Contact Acceptable		
Uses	Shrink Wrap		
RoHS Compliance	RoHS Compliant		
Forms	• Pellets		
Processing Method	Blown Film		

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.33		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength <sup>2</sup> (Yield)	6260	psi	ASTM D638	
Tensile Elongation <sup>2</sup> (Break)	170	%	ASTM D638	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	1.8	ft·lb/in	ASTM D256	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D)	74		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Vicat Softening Temperature	169	°F	ASTM D1525	

#### **Notes**

### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

#### Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 4/22/2014

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>&</sup>lt;sup>2</sup> 9.8 in/min