

- Rigid Polyvinyl Chloride

302

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Features	Good Impact Resistance			
Uses	Conduit	Piping	• Profiles	
Forms	Granules			
Processing Method	 Extrusion 			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.42		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Yield)	7250	psi	ASTM D638	
Tensile Elongation ² (Break)	160	%	ASTM D638	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	0.55	ft·lb/in	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Vicat Softening Temperature	205	°F	ASTM D1525	
Thermal Stability ³ (374°F)	> 1	hr	BS 2782	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100

Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 1/2/2013

¹ Typical properties: these are not to be construed as specifications.

² 9.8 in/min

³ Congo Red