

703A

- Rigid Polyvinyl Chloride

Thursday, June 29, 2017

General Information		
General		
Material Status	Commercial: Active	
Availability	Asia Pacific	
Features	Good Impact Resistance	
Uses	Fittings	
RoHS Compliance	RoHS Compliant	
Forms	Pellets	
Processing Method	Injection Molding	

ASTM & ISO Properties 1

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.40		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ² (Yield)	6960	psi	ASTM D638
Tensile Elongation ² (Break)	100	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	1.1	ft·lb/in	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	192	°F	ASTM D1525

Notes

¹ Typical properties: these are not to be construed as specifications.

² 9.8 in/min

Teknor Apex Company Corporate Headquarters

505 Central Avenue

Phone: 401-725-8000 Fax: 401-725-8095

In U.S. for Vinyls, TPEs, Colorants,

Pawtucket, Rhode Island 02861 U.S.

Toll Free (U.S. only) 800-556-3864

Engineered Thermoplastics (Chem Polymer)

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 4/3/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.