

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	Oil Resistant		
Uses	Gaskets Liners		
Forms	Granules		
Processing Method	Extrusion		

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.21		ASTM D792	
Congo Red (374°F)	30.0	min	BS 2782	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	2180	psi	ASTM D638	
Tensile Elongation (Break)	300	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	68		ASTM D2240	

Notes

319

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 10/7/2014

¹ Typical properties: these are not to be construed as specifications.