

- Polyethylene Friday, June 30, 2017

# **General Information**

## **Product Description**

SINPOLENE MBB1411 is a modified copolymer based black masterbatch designed specifically for use in injection moulding and extrusion of polyolefins, polystyrene and ABS. SINPOLENE MBB1411 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB1411 is delivered as free flowing pellets for processing convenience.

## **CHARACTERISTICS**

- \* Easy processing
- \* Good dispersion
- \* High jetness
- \* Minimal wear effect on processing equipment

General		
Material Status	Commercial: Active	
Availability	Asia Pacific	
Features	<ul> <li>Recyclable Material</li> </ul>	
Uses	<ul> <li>Compounding</li> </ul>	Masterbatch
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>	
Appearance	Black	
Forms	• Pellets	
Processing Method	Compounding	Injection Molding

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value Unit	Test Method		
Specific Gravity	1.16	ASTM D792		
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	< 30 g/10 min	ASTM D1238		
Carbon Black Content	> 40 %	ASTM D1603		
Moisture Content	< 0.25 %	ASTM D3030		
Additional Information				

# Additional Information

Recommended dosage: 1 - 3%

# **Notes**

## Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 5/30/2014

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.