

- Rigid Polyvinyl Chloride

Thursday, June 29, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Uses	Electrical Parts Fittings			
RoHS Compliance	RoHS Compliant			
Forms	Granules			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.48		ASTM D792	
Congo Red (374°F)	30.0	min	BS 2782	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	6960	psi	ASTM D638	
Tensile Elongation (Break)	100	%	ASTM D638	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	1.1	ft·lb/in	ASTM D256	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D)	80		ASTM D2240	
Burometer Haraness (Ghore B)	00		7.0 TW B22	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 9/23/2011

¹ Typical properties: these are not to be construed as specifications.