

Sinvicomp SRP3004FRF

- Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information			
General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	Flame Retardant		
Uses	Ceiling Panels Profiles		
RoHS Compliance	RoHS Compliant		
Forms	Granules		
Processing Method	Injection Molding		

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.43		ASTM D792	
Congo Red (374°F)	30.0	min	BS 2782	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	5660	psi	ASTM D638	
Tensile Elongation (Break)	150	%	ASTM D638	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	0.92	ft·lb/in	ASTM D256	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D)	79		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Vicat Softening Temperature	201	°F	ASTM D1525 ²	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 4/20/2014

¹ Typical properties: these are not to be construed as specifications.

² Loading 1 (10 N)