

- Rigid Polyvinyl Chloride

Thursday, June 29, 2017

General Information					
General					
Material Status	 Commercial: Active 				
Availability	Asia Pacific				
Features	Good Impact Resistance				
Uses	• Foam	Profiles			
Forms	• Powder				
Processing Method	 Extrusion 				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Bulk Factor	0.65		ASTM D1895		
Mechanical	Nominal Value	Unit	Test Method		
Flexural Modulus	31900	psi	ISO 178		
Thermal	Nominal Value	Unit	Test Method		
Vicat Softening Temperature	174	°F	ASTM D1525		
Heat Stability (356°F)	1.0	hr	ASTM D2115		

Notes

704

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)

505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 8/26/2013

¹ Typical properties: these are not to be construed as specifications.