TEKNOR APEX

# Sinvicomp SIZ5306

- Flexible Polyvinyl Chloride

Thursday, June 29, 2017

### **General Information**

#### **Product Description**

"Sinvicomp" SIZ 5306 is a wire & cable polyvinylchloride compound available in pellet form. SIZ 5306 provides good performance for insulation of electrical wires.

General	
Material Status	Commercial: Active
Availability	Asia Pacific
Uses	Insulation
Wire Types (BS 6746)	• Tl1 • Tl2
RoHS Compliance	RoHS Compliant
Forms	Pellets
Processing Method	Extrusion

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity <sup>2</sup>	1.44		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	2470	psi	IEC 811-1-1	
Tensile Elongation (Break)	280	%	IEC 811-1-1	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	85		ASTM D2240	
Aging	Nominal Value	Unit	Test Method	
Mechanical Properties After Aging in Air Oven, 176°F, 168 hr <sup>3</sup>			IEC 811-1-2	
Change in Tensile Elongation	15	%		
Change in Tensile Strength	10	%		
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity (68°F)	1.0E+14	ohms∙cm	BS 2782	
Additional Information	Nominal Value	Unit	Test Method	
Loss of Mass - Oven Ageing Condition @ 80 ± 2°C for 7 days	1.20	mg/cm <sup>2</sup>	IEC 811-3-2	

Typical temperature profile for SINVICOMP compound is from 160°C to 170°C. The optimum temperatures depend on the type of machine as well as screw design being used to process SINVICOMP.

Feeding zone: 150°C Mixing zone: 160°C~165°C Metering zone: 165°C~170°C Nozzle/Die Zone: 170°C

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.	
<sup>2</sup> @ 23°C	用公司
<sup>3</sup> @ 80 ± 2°C	小科技有限及分期商
	上语化的 上语化的 和EKNOR APEX 特诺尔爱顺利 TEKNOR APEX 特诺尔爱顺利 TEKNOR APEX 特诺尔爱顺利 TEKNOR APEX 特诺尔爱顺利 TEKNOR APEX 特诺尔爱顺利 基本语言: 021-560

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

# Sinvicomp SIZ5306

## - Flexible Polyvinyl Chloride

#### Teknor Apex Company Corporate Headquarters

Tat

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 10/9/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.