

# APEX® 80851-B

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

## **General Information**

General				
Material Status	Commercial: Active			
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America	
Uses	Wire & Cable Applications			
Wire Types	• THHN • THW	• THWN • TW		
Agency Ratings	UL QMTT2			
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>			
Appearance	Opaque			
Forms	Pellets			

ASTM & ISO Properties <sup>1</sup>					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.30		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	3300	psi	ASTM D638		
Tensile Elongation (Break)	330	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	71		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	-27.4	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity (122°F)	3.0E+14	ohms∙cm	ASTM D257		
Dielectric Constant			ASTM D150		
1 kHz	4.26				
1 MHz	3.01				
Dissipation Factor			ASTM D150		
1 kHz	0.076				
1 MHz	0.053				
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	28	%	ISO 4589-2		

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd. Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.