

# Terraloy™ MB-10000A

# Teknor Apex Company - Thermoplastic Starch + LLDPE

Friday, June 30, 2017

## **General Information**

#### **Product Description**

Terraloy MB-10000A is a Thermoplastics Starch/LLDPE masterbatch that contains up to 50% of TPS renewable content. Melt index (E) for LLDPE for the masterbatch is 0.9. This compound is for blown film application. Recommended letdown ratio with LLDPE is 1:1.

General			
Material Status	Commercial: Active		
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America
Features	Renewable Resource Cor	ntent	
Uses	<ul> <li>Masterbatch</li> </ul>		
Forms	• Pellets		
Processing Method	Blown Film		

ASTM & ISO Properties <sup>1</sup>					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.13		ASTM D792		
Melt Mass-Flow Rate (MFR) (210°C/2.16 kg)	1.5	g/10 min	ASTM D1238		
Biobased Content	< 50.0				
Thermal	Nominal Value	Unit	Test Method		
Peak Melting Temperature	257	°F	ASTM D3418		
Additional Information	Nominal Value	Unit			
Let Down Ratio - with LLDPE	1:1				

### Notes

#### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.