

APEX® 3315-NT

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information						
General						
Material Status	Commercial: Active					
Availability	Africa & Middle EastAsia Pacific	EuropeLatin America	North America			
Uses	Wire & Cable Applications					
RoHS Compliance	 RoHS Compliant 					
Appearance	Opaque					
Forms	• Pellets					

ASTM & ISO Properties ¹						
Physical	Nominal Value	Unit	Test Method			
Specific Gravity	1.22		ASTM D792			
Mechanical	Nominal Value	Unit	Test Method			
Tensile Strength (Break)	2000	psi	ASTM D638			
Tensile Elongation (Break)	430	%	ASTM D638			
Hardness	Nominal Value	Unit	Test Method			
Durometer Hardness (Shore A, 15 sec)	68		ASTM D2240			
Thermal	Nominal Value	Unit	Test Method			
Brittleness Temperature	-18.4	°F	ASTM D746			

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.