

Telcar® 1383M

Teknor Apex Company - Thermoplastic Elastomer

Friday, June 30, 2017

	General	Information			
General					
Material Status	Commercial: Active				
Availability	Africa & Middle East	• Europe	_	North America	
Availability	Asia Pacific	Latin America		• North America	
	General Purpose	High Elongation			
Features	Good ColorabilityHalogen Free	Low DensityLow Hardness	•	Medium Flow	
	<u>~</u>				
Uses	Consumer Applications Electrical/Electronic Appli	 General Purpose cations Industrial Application 	ns		
RoHS Compliance	RoHS Compliant	outono madotna rippinouton			
Appearance	Opaque				
Forms	Pellets				
Processing Method	Extrusion	Injection Molding			
Trocessing Method	LAUGION	- Injection Molaling			
	ASTM & IS	O Properties ¹			
Physical		Nominal Value	Unit	Test Method	
Specific Gravity		0.950		ASTM D792	
Melt Mass-Flow Rate (MFR) (200°C	/5.0 kg)	15	g/10 min	ASTM D1238	
Elastomers		Nominal Value	Unit	Test Method	
Tensile Strength (Break)		750	psi	ASTM D412	
Tensile Elongation (Break)		900	%	ASTM D412	
lardness		Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 1 se	c)	45		ASTM D2240	
	Drocossin	g Information			
njection	FIOCESSIII	Nominal Value	Unit		
Rear Temperature					
		340 to 380			
		340 to 380			
Middle Temperature		350 to 390	°F		
Middle Temperature Front Temperature		350 to 390 360 to 400	°F °F		
Middle Temperature Front Temperature Nozzle Temperature		350 to 390 360 to 400 370 to 410	°F °F		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp		350 to 390 360 to 400 370 to 410 370 to 410	°F °F °F		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150	°F °F °F		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000	°F °F °F		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150	°F °F °F psi		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0	°F °F °F psi		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast	°F °F °F °F psi psi rpm		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure Screw Speed Cushion		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0 50 to 100 0.150 to 1.00	°F °F °F °F psi psi punt		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure Screw Speed Cushion		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0 50 to 100 0.150 to 1.00	°F °F °F °F psi psi punt		
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure Screw Speed Cushion Extrusion		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0 50 to 100 0.150 to 1.00	°F °F °F °F psi psi punt	及分割商	
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure Screw Speed Cushion Extrusion Cylinder Zone 1 Temp.		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0 50 to 100 0.150 to 1.00	°F °F °F °F psi psi punt	公司 及分销商 58958519	
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure Screw Speed Cushion Extrusion Cylinder Zone 1 Temp. Cylinder Zone 2 Temp.		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0 50 to 100 0.150 to 1.00	°F °F °F °F psi psi punt	公司 取分销商 58958519	
Middle Temperature Front Temperature Nozzle Temperature Processing (Melt) Temp Mold Temperature Injection Pressure Injection Rate Back Pressure Screw Speed Cushion Extrusion Cylinder Zone 1 Temp. Cylinder Zone 2 Temp. Cylinder Zone 3 Temp.		350 to 390 360 to 400 370 to 410 370 to 410 77 to 150 200 to 1000 Moderate-Fast 25.0 to 50.0 50 to 100 0.150 to 1.00	°F °F °F °F psi psi punt	及分韻商 58958519	

Revision Date: 6/1/2016

Telcar® 1383M

Teknor Apex Company - Thermoplastic Elastomer

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 6/1/2016