

APEX® RM 8114

Teknor Apex Company - Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	High Impact Resistance				
Agency Ratings	• UL 94 V0				
Forms	Pellets				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.31		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Modulus	360000	psi	ASTM D638		
Tensile Strength (Break)	6330	psi	ASTM D638		
Flexural Modulus	355000	psi	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (73°F, 0.125 in)	14	ft·lb/in	ASTM D256		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D, 10 sec)	80		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load			ASTM D648		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

264 psi, Unannealed

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



152 °F

Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.