

PVC Film 165-J3 NT

Teknor Apex Company - Flexible Polyvinyl Chloride

Thursday, June 29, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	Africa & Middle East	• Europe	North America		
	 Asia Pacific 	 Latin America 			
Features	 Non-Phthalate - Citrate Plasticizer 	Steam Sterilizable			
Uses	Medical/Healthcare Applications				
Forms	• Film				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.27		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2700	psi	ASTM D638		
Tensile Elongation (Break)	350	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	84		ASTM D2240		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 7/25/2014

¹ Typical properties: these are not to be construed as specifications.