TEKNOR APEX

APEX[®] 79-B427D-25

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information General Material Status · Commercial: Active · Africa & Middle East • Europe North America Availability · Asia Pacific Latin America Uses · Automotive Exterior Parts • GM GMP.PVC.010 Automotive Specifications Forms · Pellets · Injection Molding **Processing Method**

ASTM & ISO Properties¹

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2380	psi	ASTM D638
Tensile Elongation (Break)	430	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	78		ASTM D2240

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex U.K. Ltd.
	Tat Bank Road
In U.S. for Vinyls, TPEs, Colorants,	Oldbury, West Midlands B69 4NH England
Engineered Thermoplastics (Chem Polymer)	
505 Central Avenue	Phone: (44) 121-665-2100
Pawtucket, Rhode Island 02861 U.S.	Fax: (44) 121-544-5530
Phone: 401-725-8000	
Fax: 401-725-8095	etpsales@teknorapex.co.uk
Toll Free (U.S. only) 800-556-3864	

info@teknorapex.com



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.