

## APEX® RE 8103R-NT

## Teknor Apex Company - Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Forms	Pellets				

ASTM & ISO Properties <sup>1</sup>					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.32		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Modulus <sup>2</sup>	372000	psi	ASTM D638		
Tensile Strength <sup>2</sup> (Break)	5050	psi	ASTM D638		
Tensile Elongation (Break)	100	%	ASTM D638		
Flexural Modulus <sup>3</sup>	321000	psi	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (73°F, 0.125 in, Injection Molded)	0.89	ft·lb/in	ASTM D256		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D, 10 sec)	79		ASTM D2240		

## **Notes**

## Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>&</sup>lt;sup>2</sup> 0.20 in/min

<sup>3 0.050</sup> in/min