

- Linear Low Density Polyethylene

General Information

Product Description

Sinpolene MBW0661 is a polyethylene-based white masterbatch designed specifically for use in tubular film blowing, blow moulding and extrusion of polyolefins. With its high pigment loading, Sinpolene MBW0661 offers high colouring value with excellent quality and performance.

Sinpolene MBW0661 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High opacifying power
- * Excellent whiteness

General

Material Status	• Commercial: Active		
Availability	• Asia Pacific		
Filler / Reinforcement	• Titanium Dioxide, 60% Filler by Weight		
Features	• General Purpose		
Uses	• Film	• Sheet	
RoHS Compliance	• RoHS Compliant		
Forms	• Pellets		
Processing Method	• Blown Film	• Extrusion	• Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.70		ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	< 30	g/10 min	ASTM D1238
Moisture Content	< 0.20	%	ASTM D3030

Additional Information

Recommended dosage: 2 - 5%

Notes

¹ Typical properties: these are not to be construed as specifications.

**Teknor Apex Company
Corporate Headquarters**

*In U.S. for Vinyls, TPEs, Colorants,
Engineered Thermoplastics (Chem Polymer)*
505 Central Avenue
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000
Fax: 401-725-8095
Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road
Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100
Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

