

Synres® SR-4000

Teknor Apex Company - Polypropylene

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Forms	Pellets				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.12		ASTM D792		
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	12	g/10 min	ASTM D1238		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	3700	psi	ASTM D638		
Tensile Elongation (Yield)	3.5	%	ASTM D638		
Flexural Modulus	340000	psi	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact	0.70	ft·lb/in	ASTM D256		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D, 10 sec)	70		ASTM D2240		
Additional Information					

Additional Information

Bulk Density = 48.5 lbs/ cubic foot

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.