

- Linear Low Density Polyethylene

General Information

General

Material Status	• Commercial: Active		
Availability	• Asia Pacific		
Features	• General Purpose		
Forms	• Pellets		
Processing Method	• Blown Film	• Film Extrusion	• Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.10		ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	10 to 28	g/10 min	ASTM D1238
Carbon Black Content	35	%	ASTM D1603
Moisture Content	< 0.25	%	ASTM D3030

Additional Information

Recommended dosage : 1 - 3%

Notes

¹ Typical properties: these are not to be construed as specifications.

**Teknor Apex Company
Corporate Headquarters**

*In U.S. for Vinyls, TPEs, Colorants,
Engineered Thermoplastics (Chem Polymer)*
505 Central Avenue
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000
Fax: 401-725-8095
Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road
Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100
Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

上海松翰塑化科技有限公司
 TEKNOR APEX 特诺尔爱佩斯 一级分销商
 teknorapex.shshsj.com 联系电话: 021-58958519