

872

- Low Density Polyethylene

Friday, June 30, 2017

General Information		
General		
Material Status	Commercial: Active	
Availability	Asia Pacific	
Filler / Reinforcement	Titanium Dioxide, 70% Filler by Weight	
Features	General Purpose	
Uses	Packaging	
RoHS Compliance	RoHS Compliant	
Forms	Pellets	
Processing Method	 Blow Molding Blown Film Injection Molding 	

Nominal Value Unit	Test Method
2.00	
2.00	ASTM D792
< 25 g/10 min	ASTM D1238
< 0.20 %	ASTM D3030
	•

Recommended dosage: 3 - 10%

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters Teknor Apex U.K. Ltd. In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) Tat Bank Road Oldbury, West Midlands B69 4NH England 505 Central Avenue Phone: (44) 121-665-2100 Fax: (44) 121-544-5530 Phone: 401-725-8000 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com

Toll Free (U.S. only) 800-556-3864

Fax: 401-725-8095



Revision Date: 6/19/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.