

General Information

General

Material Status	• Commercial: Active
Availability	• Asia Pacific
Features	• Medium Impact Resistance
Uses	• Electrical Parts • Fittings
Forms	• Pellets
Processing Method	• Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	6530	psi	ASTM D638
Tensile Elongation (Break)	100	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	1.1	ft-lb/in	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	192	°F	ASTM D1525

Notes

¹ Typical properties: these are not to be construed as specifications.

<p>Teknor Apex Company Corporate Headquarters</p> <p><i>In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)</i></p> <p>505 Central Avenue Pawtucket, Rhode Island 02861 U.S.</p> <p>Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864</p>	<p>Teknor Apex U.K. Ltd.</p> <p>Tat Bank Road Oldbury, West Midlands B69 4NH England</p> <p>Phone: (44) 121-665-2100 Fax: (44) 121-544-5530</p> <p>etpsales@teknorapex.co.uk</p>
---	---

info@teknorapex.com

