

- Low Density Polyethylene

Friday, June 30, 2017

General Information

Product Description

SINPOLENE MBB1402 is a modified copolymer based black masterbatch designed specifically for use in injection moulding and extrusion of polyolefins, polystyrene and ABS. SINPOLENE MBB1402 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB1402 is delivered as free flowing pellets for processing convenience. It is packed in 25 kg bags. The product should be stored in dry place.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General	
Material Status	Commercial: Active
Availability	Asia Pacific
Features	Recyclable Material
Uses	Compounding
RoHS Compliance	RoHS Compliant
Forms	• Pellets

ASTM & ISO Properties ¹			
Physical	Nominal Value Unit	Test Method	
Specific Gravity	1.16	ASTM D792	
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	< 10 g/10 min	ASTM D1238	
Carbon Black Content	> 40 %	ASTM D1603	
Moisture Content	< 0.25 %	ASTM D3030	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 6/19/2014

¹ Typical properties: these are not to be construed as specifications.