

- Linear Low Density Polyethylene

**General Information**

**General**

Material Status	• Commercial: Active
Availability	• Asia Pacific
Features	• General Purpose
Uses	• Blown Film
Forms	• Pellets
Processing Method	• Blow Molding

**ASTM & ISO Properties <sup>1</sup>**

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.16		ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	< 25	g/10 min	ASTM D1238
Carbon Black Content	45	%	ASTM D1603
Moisture Content	< 0.25	%	ASTM D3030

**Additional Information**

Recommended dosage: 2 - 4%

**Notes**

<sup>1</sup> Typical properties: these are not to be construed as specifications.

**Teknor Apex Company  
Corporate Headquarters**

*In U.S. for Vinyls, TPEs, Colorants,  
Engineered Thermoplastics (Chem Polymer)*  
505 Central Avenue  
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000  
Fax: 401-725-8095  
Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

**Teknor Apex U.K. Ltd.**

Tat Bank Road  
Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100  
Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

**上海松翰塑化科技有限公司**  
 TEKNOR APEX 特诺尔爱佩斯 一级分销商  
 teknorapex.shshsj.com 联系电话: 021-58958519