

## - Rigid Polyvinyl Chloride

Thursday, June 29, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	Asia Pacific				
Features	Good Impact Resistance				
Uses	Foam	Profiles			
Forms	Powder				
Processing Method	Extrusion				

ASTM & ISO Properties <sup>1</sup>			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.652		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	31900	psi	ISO 178
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	174	°F	ASTM D1525
Heat Stability (356°F)	1.0	hr	ASTM D2115

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex U.K. Ltd.
	Tat Bank Road
In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)	Oldbury, West Midlands B69 4NH England
505 Central Avenue	Phone: (44) 121-665-2100
Pawtucket, Rhode Island 02861 U.S.	Fax: (44) 121-544-5530
Phone: 401-725-8000	
Fax: 401-725-8095	etpsales@teknorapex.co.uk
Toll Free (U.S. only) 800-556-3864	

info@teknorapex.com



Revision Date: 1/4/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.