- Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Features	Ethylene Oxide Sterilizable Non-DEHP Plasticizer			
Uses	Medical/Healthcare Applications			
Forms	• Pellets			
Processing Method	• Extrusion			

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.23		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Break)	2610	psi	ASTM D638	
Tensile Elongation (Break)	380	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness	90		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Heat Stability (374°F)	> 30.0	min	ASTM D2115-92	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Phone: 401-725-8000

Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Pawtucket, Rhode Island 02861 U.S.

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 10/7/2014

¹ Typical properties: these are not to be construed as specifications.

² 20 in/min