

05

- Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Features	Ethylene Oxide Sterilizable			
Uses	Medical/Healthcare Applications			
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.16		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Yield)	1160	psi	ASTM D638	
Tensile Elongation (Break)	380	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	50		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Heat Stability (374°F)	> 30.0	min	ASTM D2115-92	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

info@teknorapex.com

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100

Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 10/7/2014

¹ Typical properties: these are not to be construed as specifications.

² 20 in/min