

APEX® RM 9012

Teknor Apex Company - Rigid Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Forms	Pellets				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.46		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Modulus ²	463000	psi	ASTM D638		
Tensile Strength ² (Break)	6320	psi	ASTM D638		
Tensile Elongation (Break)	35	%	ASTM D638		
Flexural Modulus ³	380000	psi	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (73°F, 0.125 in, Injection Molded)	12	ft·lb/in	ASTM D256		
Drop Impact Resistance ⁴ (73°F)	2.50	in·lb/mil	ASTM D4226		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D, 10 sec)	82		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load			ASTM D648		
264 psi, Annealed, 0.250 in	159	°F			

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

² 0.20 in/min

³ 0.050 in/min

⁴ Procedure A, TUP