

APEX® 55302 Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

General			
Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America
Features	General Purpose		
Uses	Communication Wire Jacketing Telephone Retractile Cord Jacketing		
RoHS Compliance	RoHS Compliant		
Appearance	Opaque		
Forms	Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.22		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2250	psi	ASTM D638	
Tensile Elongation (Break)	400	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	74		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-50.8	°F	ASTM D746	
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	24	%	ASTM D2863	
Additional Information				

Additional information

Formerly Apex 302

Temperature Rating: 80 °C

UL Sunlight Resistance Recognition: No Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 100°C: 100 % Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 100°C: 102 %

Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 113°C: 80 %

Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 113°C: 108 %

Processing Information			
Extrusion	Nominal Value Unit		
Melt Temperature	345 °F		
Notes			
¹ Typical properties: these are not to be construed as specifications.	四公司		
	上海松静建化料技有限公司 上海松静建化料成有限公司 于EKNOR APEX特诺尔爱佩斯-级分销商 TEKNOR APEX 特诺尔爱佩斯级分销商 TEKNOR APEX 特诺尔爱佩斯		
	如此朝望化市东爱佩和121-585°		
	LIBIA APEX Com ##		
	TEKINGAPEX.SIL		

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

APEX® 55302

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.