

APEX® 327

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

| General Information | | | | |
|---------------------|--|---|---------------|--|
| General | | | | |
| Material Status | Commercial: Active | | | |
| Availability | Africa & Middle East | • Europe | North America | |
| | Asia Pacific | Latin America | | |
| Uses | Flexible Cord Insulation | Flexible Cord Jacketing | | |
| Wire Types | • SJT | • SPT-3 | | |
| | • SPT-1 | • SRDT | • SVT | |
| | • SPT-2 | • ST | | |
| Agency Ratings | • UL 1581 | • UL 62 | | |
| RoHS Compliance | RoHS Compliant | | | |
| Appearance | Opaque | | | |
| Forms | • Pellets | | | |
| Processing Method | Extrusion | | | |

| ASTM & ISO Properties 1 | | | | |
|--------------------------------------|---------------|---------|-------------|--|
| Physical | Nominal Value | Unit | Test Method | |
| Specific Gravity | 1.43 | | ASTM D792 | |
| Mechanical | Nominal Value | Unit | Test Method | |
| Tensile Strength (Break) | 2240 | psi | ASTM D638 | |
| Tensile Elongation (Break) | 300 | % | ASTM D638 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Durometer Hardness (Shore A, 15 sec) | 85 | | ASTM D2240 | |
| Thermal | Nominal Value | Unit | Test Method | |
| Continuous Use Temperature | 176 | °F | ASTM D794 | |
| Brittleness Temperature | -20.2 | °F | ASTM D746 | |
| Electrical | Nominal Value | Unit | Test Method | |
| Volume Resistivity | 5.0E+11 | ohms·cm | ASTM D257 | |
| Flammability | Nominal Value | Unit | Test Method | |
| Oxygen Index | 24 | % | ASTM D2863 | |
| Additional Information | | | | |

Additional Information

1/32 in minimum wall thickness Temperature Rating: 80 °C

UL Sunlight Resistance Recognition: No

| Processing Information | | | |
|------------------------|--------------------|--|--|
| Extrusion | Nominal Value Unit | | |
| Melt Temperature | 360 °F | | |

Notes

¹ Typical properties: these are not to be construed as specifications.

上海松静理化料技有限公司 上海松静理化料技有限公開商 TEKNOR APEX 特诺尔曼斯斯 021-58958519 teknorapex.shshsj.com 斯泰思语: 021-58958519

Revision Date: 12/12/2013

APEX® 327

Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013