

# **APEX® 830**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

| General Information |   |   |               |  |
|---------------------|---|---|---------------|--|
| General             |   |   |               |  |
| Material Status     | Commercial: Active  |   |               |  |
| Availability        | <ul><li>Africa &amp; Middle East</li><li>Asia Pacific</li></ul> | <ul><li>Europe</li><li>Latin America</li></ul>  | North America |  |
| Features            | <ul> <li>High Heat Resistance</li> </ul>                        | <ul> <li>Low Temperature Flexibility</li> </ul> | Oil Resistant |  |
| Uses                | <ul> <li>Cable Jacketing</li> </ul>                             |   |               |  |
| Wire Types          | • SJT<br>• SRDT   | • ST<br>• SVT                                   |               |  |
| Agency Ratings      | • UL 62   |   |               |  |
| RoHS Compliance     | <ul> <li>RoHS Compliant</li> </ul>                              |   |               |  |
| Appearance          | <ul> <li>Clear/Transparent</li> </ul>                           |   |               |  |
| Forms               | • Pellets   |   |               |  |
| Processing Method   | Sheet Extrusion   |   |               |  |

| ASTM & ISO Properties <sup>1</sup>   |               |      |             |  |
|--------------------------------------|---------------|------|-------------|--|
| Physical                             | Nominal Value | Unit | Test Method |  |
| Specific Gravity                     | 1.23          |      | ASTM D792   |  |
| Mechanical                           | Nominal Value | Unit | Test Method |  |
| Tensile Strength (Break)             | 2500          | psi  | ASTM D638   |  |
| Tensile Elongation (Break)           | 360           | %    | ASTM D638   |  |
| Hardness                             | Nominal Value | Unit | Test Method |  |
| Durometer Hardness (Shore A, 15 sec) | 83            |      | ASTM D2240  |  |
| Thermal                              | Nominal Value | Unit | Test Method |  |
| Continuous Use Temperature           | 221           | °F   | ASTM D794   |  |
| Brittleness Temperature              | -43.6         | °F   | ASTM D746   |  |
| Flammability                         | Nominal Value | Unit | Test Method |  |
| Oxygen Index                         | 23            | %    | ASTM D2863  |  |
|                                      |               |      |             |  |

#### **Additional Information**

Temperature Rating: 105 °C

UL Sunlight Resistance Recognition: No

Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 136°C: 87 % Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 136°C: 102 %

| Processing Information |                    |  |  |
|------------------------|--------------------|--|--|
| Extrusion              | Nominal Value Unit |  |  |
| Melt Temperature       | 355 °F             |  |  |

#### **Notes**

<sup>1</sup> Typical properties: these are not to be construed as specifications.

上海松翰理化科技有限公司 TEKNOR APEX 特诺尔曼佩斯 021-58958519 teknorapex.shshsj.com 麻素患症: 021-58958519

Revision Date: 12/12/2013

### **APEX® 830**

### Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013