

APEX® 4130 Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information

Material Status	 Commercial: Active 			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Features	Sunlight Resistant (720 hours) • UV Resistant			
Uses	Flexible Cord Jacketing			
Wire Types	• SJT • SJTW	• SRDT • ST	• STW • SVT	
Agency Ratings	UL QMTT2			
RoHS Compliance	RoHS Compliant			
Appearance	• Opaque			
Forms	Pellets			
Processing Method	Extrusion			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.39		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2600	psi	ASTM D638	
Tensile Elongation (Break)	360	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	83		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	167	°F	ASTM D794	
Brittleness Temperature	-16.6	°F	ASTM D746	
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	29	%	ASTM D2863	
Additional Information				

Prime suggestion Temperature Rating: 80 °C

UL Sunlight Resistance Recognition: 720 hr

Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 113°C: 86 %

Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 113°C: 110 %

Processing Information				
Extrusion	Nominal Value Unit			
Melt Temperature	355 °F			
Notes	一個公司			
¹ Typical properties: these are not to be construed as specifications.	中心科技有PR 级分销商			
	上海松朝望化科技有限公前 用子子的 上海松朝望 化科技有限 一般分销商 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面 -现分前面			

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.

APEX® 4130

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex Company - Flexible Polyvinyl Chloride

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.