

APEX® 77-W002-A Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General			
Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America
Features	 Fungus Resistant 	Low Temperature Flexib	ility
Uses	 Military Applications 	Tubing	
Agency Ratings	MIL I-631-D, Grade A, Class I, Form U, Type F		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.22		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (100% Strain)	1390	psi	ASTM D638	
Tensile Strength (Break)	2400	psi	ASTM D638	
Tensile Elongation (Break)	420	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	81		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-47.2	°F	ASTM D746	
Flammability	Nominal Value	Unit	Test Method	
Oxygen Index	24	%	ASTM D2863	
Additional Information				

Temperature Rating: 80 °C

Insulation Resistance, Mohm/1000 ft: .1e12

Ultimate Elongation Retained, UL 1581, Oven Aged, 7 days, 113°C: 73 %

Tensile Strength Retained, UL 1581, Oven Aged, 7 days, 113°C: 108 %

Processing Information

Extrusion	Nominal Value Unit
Melt Temperature	355 °F

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex U.K. Ltd.	
• •	Tat Bank Road	AVE!
In U.S. for Vinyls, TPEs, Colorants,	Oldbury, West Midlands B69 4NH England	「日の見る」は商
Engineered Thermoplastics (Chem Polymer)		115月10日分報
505 Central Avenue	Phone: (44) 121-665-2100	1V 7 + 7 - 50 - 58510
Pawtucket, Rhode Island 02861 U.S.	Fax: (44) 121-544-5530	小前望107万震顺和021-580
Phone: 401-725-8000		EXTLAPSOEX POLEXEBIL
Fax: 401-725-8095	etpsales@teknorapex.co.uk	RAP si com
Toll Free (U.S. only) 800-556-3864	-f	上海松翰裡化科技有如 43分鹃的 上海松翰 20158958619 TEKNOR APEX 特诺尔爱佩斯 - 级分鹃的 TEKNOR APEX 特诺尔爱佩斯 - 021-58958619 Teknorapex.shensj.com 联系电底: 021-58958619
		ten
info@teknorapex.com		

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with selfer's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.