

APEX® 1877

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
General					
Material Status	Commercial: Active				
Availability	Africa & Middle East	• Europe	North America		
	 Asia Pacific 	 Latin America 	North America		
Features	 General Purpose 				
Uses	Cable Jacketing	 Wire & Cable Applications 			
	 General Purpose 	 Wire Jacketing 			
RoHS Compliance	 RoHS Compliant 				
Forms	• Pellets				
Processing Method	 Extrusion 				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.35		ASTM D792		
Molding Shrinkage - Flow	0.010 to 0.012	in/in	ASTM D955		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2400	psi	ASTM D638		
Tensile Elongation (Break)	270	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	75		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	5.00	°F	ASTM D746		
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	29	%	ASTM D2863		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000

Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

Ton Tree (o.e. only) oo

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100

Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.