

Chemlon® JW21

Teknor Apex Company (Chem Polymer) - Polyamide 6

Friday, June 30, 2017

General Information

Product Description

JW21 is a medium viscosity grade of nylon 6 designed for wire coating extrusion. JW21 is heavily pigmented and is designed to provide good opacity even with thin coatings. It also features a lubrication system that is designed to ensure excellent adhesion between the wire and the coating - as well as optimal processing characteristics at high line speeds. JW21 is available in a range of colours - including heavy metal free options.

General

Material Status	• Commercial: Active
Availability	• Europe
Additive	• Lubricant
Features	• Good Adhesion • Good Processability • Lubricated • Medium Viscosity
Uses	• Wire & Cable Applications
Appearance	• Colors Available
Processing Method	• Wire & Cable Extrusion

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density	1.14 to 1.38	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	435000 to 522000	psi	ISO 178
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (264 psi, Unannealed)	185 to 203	°F	ISO 75-2/A
Additional Information	Nominal Value	Unit	Test Method
Filler Content	0.0 to 25	%	Internal Method

Processing Information

Extrusion	Nominal Value	Unit
Drying Temperature	176	°F
Drying Time	20	hr
Cylinder Zone 1 Temp.	482 to 572	°F
Cylinder Zone 3 Temp.	482 to 572	°F
Cylinder Zone 5 Temp.	482 to 572	°F
Melt Temperature	482 to 572	°F

Extrusion Notes

No drying is necessary unless the material has been exposed to air for longer than three hours. The appearance of splash marks on the surface of mouldings indicates excessive moisture is present.

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants,
Engineered Thermoplastics (Chem Polymer)
505 Central Avenue
Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000
Fax: 401-725-8095
Toll Free (U.S. only) 800-556-3864

info@teknorapex.com

Teknor Apex U.K. Ltd.

Tat Bank Road
Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100
Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk



Revision Date: 3/25/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.