🚸 TEKNOR APEX

APEX® 90-A482R-65-NT

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America	
Uses	Medical/Healthcare Applications			
Forms	Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹				
Physical	Nominal Value Unit	Test Method		
Specific Gravity	1.17	ASTM D792		
Mechanical	Nominal Value Unit	Test Method		
Tensile Strength (Break)	1600 psi	ASTM D638		
Tensile Elongation (Break)	400 %	ASTM D638		
Hardness	Nominal Value Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	65	ASTM D2240		

Notes

¹ Typical properties: these are not to be construed as specifications.

Teknor Apex Company Corporate Headquarters	Teknor Apex U.K. Ltd.
	Tat Bank Road
In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer)	Oldbury, West Midlands B69 4NH England
505 Central Avenue	Phone: (44) 121-665-2100
Pawtucket, Rhode Island 02861 U.S.	Fax: (44) 121-544-5530
Phone: 401-725-8000	
Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864	etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.