

## APEX® 90-A471R-90-NT

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

| General Information |   |   |                        |  |  |
|---------------------|---|---|------------------------|--|--|
| General             |   |   |                        |  |  |
| Material Status     | Commercial: Active  |   |                        |  |  |
| Availability        | <ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul> | <ul><li>Europe</li><li>Latin America</li></ul>  | North America          |  |  |
| Additive            | <ul> <li>Plasticizer</li> </ul>                                   |   |                        |  |  |
| Features            | <ul> <li>DEHP Plasticizer</li> </ul>                              | <ul> <li>Radiation (Gamma) Resistant</li> </ul> | Radiation Sterilizable |  |  |
| Uses                | Medical/Healthcare Applications • Tubing                          |   |                        |  |  |
| Appearance          | <ul> <li>Clear/Transparent</li> </ul>                             |   |                        |  |  |
| Forms               | • Pellets   |   |                        |  |  |
| Processing Method   | <ul> <li>Extrusion</li> </ul>                                     |   |                        |  |  |

| ASTM & ISO Properties <sup>1</sup>   |               |      |             |  |  |
|--------------------------------------|---------------|------|-------------|--|--|
| Physical                             | Nominal Value | Unit | Test Method |  |  |
| Specific Gravity                     | 1.27          |      | ASTM D792   |  |  |
| Mechanical                           | Nominal Value | Unit | Test Method |  |  |
| Tensile Strength (Break)             | 3350          | psi  | ASTM D638   |  |  |
| Tensile Elongation (Break)           | 360           | %    | ASTM D638   |  |  |
| Hardness                             | Nominal Value | Unit | Test Method |  |  |
| Durometer Hardness (Shore A, 15 sec) | 90            |      | ASTM D2240  |  |  |

## **Notes**

## Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Tawadka, Midde Island 02001 0.0

Phone: 401-725-8000 Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864 Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.