

APEX® 1521

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
Product Description					
Applications include automotive pa	rts, auto plugs, and grommets.				
General					
Material Status	Commercial: Active				
Availability	Africa & Middle East	• Europe	North America		
	 Asia Pacific 	 Latin America 			
Features	 General Purpose 	Low Gloss			
Uses	 Automotive Applications 	High Temperature Application	ons		
Automotive Specifications	FORD ESB-M4D259-A Type I	• FORD ESB-M4D259-B1	 FORD ESB-M4D317-A Type I 		
Appearance	Natural Color	Opaque			
Forms	• Pellets				
Processing Method	Injection Molding				

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.20		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	1220	psi	ASTM D638	
Tensile Elongation (Break)	460	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	52		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-47.2	°F	ASTM D746	

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.