

# **APEX® 1524**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
Product Description				
Applications include automotive pa	rts, auto plugs, and grommets.			
General				
Material Status	Commercial: Active			
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America	
Features	<ul> <li>General Purpose</li> </ul>	Low Gloss		
Uses	<ul> <li>Automotive Applications</li> </ul>	High Temperature Applications		
Automotive Specifications	<ul> <li>CHRYSLER MS-DC-227 CPN1999 Color: Black</li> </ul>	FORD ESB-M4D317-A Type IV		
Appearance	<ul> <li>Natural Color</li> </ul>	<ul> <li>Opaque</li> </ul>		
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.29		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	1900	psi	ASTM D638	
Tensile Elongation (Break)	400	%	ASTM D638	
Elastomers	Nominal Value	Unit	Test Method	
Tear Strength	220	lbf/in	ASTM D624	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	74		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-31.0	°F	ASTM D746	

## Notes

### Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000

Fax: 401-725-8095 Toll Free (U.S. only) 800-556-3864

#### Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.