

## **APEX® 1590**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

	General In	formation	
Product Description			
Applications include appliance	parts, bumpers, suction cups, and promotio	n items.	
General			
Material Status	Commercial: Active		
Availability	<ul><li>Africa &amp; Middle East</li><li>Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America
Features	<ul> <li>General Purpose</li> </ul>		
Uses	<ul> <li>Appliance Components</li> </ul>	<ul> <li>General Purpose</li> </ul>	
Appearance	<ul> <li>Clear/Transparent</li> </ul>		
Forms	• Pellets		
Processing Method	Injection Molding		

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.24		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2800	psi	ASTM D638		
Tensile Elongation (Break)	300	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	90		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	1.40	°F	ASTM D746		

## **Notes**

## Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.