

APEX® 1700-65

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

	, ,		
	General In	formation	
Product Description			
Low gloss appearance for application	cations including furniture trim, footwear, a	nd appliance parts.	
General			
Material Status	Commercial: Active		
Availability	Africa & Middle East	• Europe	North America
	 Asia Pacific 	 Latin America 	North America
Features	 General Purpose 	Low Gloss	
Uses	 Appliance Components 	 Footwear 	Furniture
Forms	• Pellets		
Processing Method	Injection Molding		

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.18		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	1450	psi	ASTM D638		
Tensile Elongation (Break)	330	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	65		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	-45.4	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.