

APEX® 1700-90

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information				
Product Description				
Low gloss appearance for application	cations including furniture trim, footwear, ar	nd appliance parts.		
General				
Material Status	Commercial: Active			
Availability	 Africa & Middle East 	• Europe	North America	
	 Asia Pacific 	 Latin America 	North America	
Features	 General Purpose 	Low Gloss		
Uses	 Appliance Components 	 Footwear 	Furniture	
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties ¹				
Physical	Nominal Value Unit	Test Method		
Specific Gravity	1.27	ASTM D792		
Mechanical	Nominal Value Unit	Test Method		
Tensile Strength (Break)	3040 psi	ASTM D638		
Tensile Elongation (Break)	290 %	ASTM D638		
Hardness	Nominal Value Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	90	ASTM D2240		
Thermal	Nominal Value Unit	Test Method		
Brittleness Temperature	-11.2 °F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.