

APEX® 585

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information						
Product Description						
Applications include tubing, she	et and film, wire coating, and strip doors.					
General						
Material Status	Commercial: Active					
Availability	Africa & Middle EastAsia Pacific	EuropeLatin America	North America			
Features	 General Purpose 					
Uses	Tubing	Wire Jacketing				
Wire Types	• SPT-1	• SPT-2				
Agency Ratings	• UL 498	• UL 62				
RoHS Compliance	 RoHS Compliant 					
Appearance	 Clear/Transparent 					
Forms	• Pellets					
Processing Method	 Extrusion 					

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.21		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2500	psi	ASTM D638		
Tensile Elongation (Break)	380	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	80		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	122	°F	ASTM D794		
Brittleness Temperature	-34.6	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Phone: 401-725-8000

Fax: (44) 121-544-5530

Phone: (44) 121-665-2100

Oldbury, West Midlands B69 4NH England

Teknor Apex U.K. Ltd.

Tat Bank Road

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.