

APEX® 3164

Teknor Apex Company - Flexible Polyvinyl Chloride

Friday, June 30, 2017

General Information					
Product Description					
Applications include weather-str	rip, spline, profiles, "T" moldings.				
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	 General Purpose 				
Uses	 Hose Profiles	 Tubing Weatherstripping			
Appearance	Natural Color	• Opaque			
Forms	• Pellets				
Processing Method	 Extrusion 				

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.35		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	1400	psi	ASTM D638		
Tensile Elongation (Break)	390	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	64		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Brittleness Temperature	-45.4	°F	ASTM D746		

Notes

Teknor Apex Company Corporate Headquarters

In U.S. for Vinyls, TPEs, Colorants, Engineered Thermoplastics (Chem Polymer) 505 Central Avenue

Pawtucket, Rhode Island 02861 U.S.

Phone: 401-725-8000 Fax: 401-725-8095

Toll Free (U.S. only) 800-556-3864

Teknor Apex U.K. Ltd.

Tat Bank Road

Oldbury, West Midlands B69 4NH England

Phone: (44) 121-665-2100 Fax: (44) 121-544-5530

etpsales@teknorapex.co.uk

info@teknorapex.com



Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.